

LOAD DATA SUMMARY

SYSTEM	MAIN RUNNER 1	PRIMARY CROSS TEE 2	SECONDARY CROSS TEE 3	MAX. LOAD kg/m ²
PRELUDE 24 XL ²	BP 31 40 32 A	BP 31 30 51 B	BP 31 20 21 A	10,5
PRELUDE 24 TL	BP 31 40 32 A	BP 11 30 32 C	BP 11 20 32 C	10,5
PRELUDE 24 XL ² (1800 space)	BP 31 40 32 A	BP 31 34 31	BP 31 20 21 A	5,0
PRELUDE 24 TL (1800 space)	BP 31 40 32 A	BP 11 34 33 D	BP 11 20 32 C	4,9
PRELUDE 24 NC with TL	BP 28 40 33 A	BP 14 30 33 C	BP 14 20 33 C	8,7
PRELUDE 60 with 24 XL ²	BP 40 40 94	BP 31 30 51 B	BP 31 20 21 A	14,1
PRELUDE 15 XL ²	BP 30 40 33 A	BP 30 30 33 B	BP 30 20 33 B	10,4
PRELUDE 15 TL	BP 30 40 33 A	BP 10 30 33 A	BP 10 20 33 A	10,4
SILHOUETTE XL ²	BP 80 40 42	BP 80 30 42	BP 80 20 42	8,9
INTERLUDE XL ²	BP 61 40 42	BP 61 30 42	BP 61 20 42	11,5
T35	BP 12 40 33 A	BP 12 30 33 A	BP 12 20 33 A	9,2

For hangers at 1200mm centres, using "ladder" type layout (span / deflection = L/500 but not more than 4mm, tested in accordance with EN 13964).

